

03/11/99
10376 U.S. PTO

FISH & RICHARDSON P.C.

Frederick P. Fish
1855-1930

W.K. Richardson
1859-1951

March 11, 1999

Attorney Docket No.: 07844/292001

103518 U.S. PTO
09/266680
03/11/99

225 Franklin Street
Boston, Massachusetts
02110-2804

Telephone
617 542-5070

Facsimile
617 542-8906

Web Site
www.fr.com

Box Patent Application
Assistant Commissioner for Patents
Washington, DC 20231

Presented for filing is a new original patent application of:

BOSTON

NEW YORK

SILICON VALLEY

SOUTHERN CALIFORNIA

TWIN CITIES

WASHINGTON, D.C.

Applicant: JEFF YOUNG AND JOEL A. NAVA
Title: METHOD OF CONSTRUCTING A DOCUMENT TYPE
DEFINITION FROM A SET OF STRUCTURED
ELECTRONIC DOCUMENTS

Enclosed are the following papers, including all those required to receive a filing date under 37 CFR §1.53(b):

	<u>Pages</u>
Specification	18
Claims	8
Abstract	1
Declaration	2
Drawing(s)	9

Enclosures:

- Postcard.
- Assignments (2) ; Assignment Recordation cover sheet.

Basic filing fee	\$ 760.00
Total claims in excess of 20 times \$18.00	144.00

"EXPRESS MAIL" Mailing Label Number EL182578351
Date of Deposit March 11, 1999
I hereby certify under 37 CFR 1.10 that this correspondence is being
deposited with the United States Postal Service as "Express Mail Post
Office To Addressee" with sufficient postage on the date indicated
above and is addressed to the Assistant Commissioner for Patents,
Washington, D.C. 20231.

Jason Kurian

JM

FISH & RICHARDSON P.C.

BOX PATENT APPLICATION

March 11, 1999

Page 2

Independent claims in excess of 3 times \$78.00	312.00
Multiple dependent claims	0.00
Total filing fee:	\$ 1216.00

A check for the filing fee is enclosed. Please apply any other required fees or any credits to deposit account 06-1050, referencing the attorney docket number shown above.


If this application is found to be INCOMPLETE, or if a telephone conference would otherwise be helpful, please call the undersigned at 617/542-5070.

Kindly acknowledge receipt of this application by returning the enclosed postcard.

Please send all correspondence to:

Roger S. Borovoy
Fish & Richardson P.C.
2200 Sand Hill Road, Suite 100
Menlo Park, CA 94025

Respectfully submitted,



Denis G. Maloney
Reg. No. 29,670

Enclosures
356156-1

METHOD OF CONSTRUCTING A DOCUMENT TYPE DEFINITION
FROM A SET OF STRUCTURED ELECTRONIC DOCUMENTS

BACKGROUND OF THE INVENTION

5 The present invention relates generally to electronic
document processing.

Numerous publishing systems have been developed to assist in the production of structured electronic documents. These publishing systems contain document authoring tools such as text editors which allow a publisher to add descriptive markup to an electronic document. The descriptive markup assigns meaning to various regions of an electronic document. For instance, some paragraphs may be marked as body paragraphs, while others are marked as headings. The structure of such electronic documents may or may not be hierarchical. For example, various marked regions may contain other regions, such as a section containing several sub-sections, each of which contain a heading and one or more paragraphs. These marked regions are referred to as elements, each of which has a particular type (e.g., paragraph). Because descriptive markup defines a document's structure as including a set of element types which, when taken together, typically form a tree or similar hierarchical object, the tree of element types is often referred to as the document's "structure".

20 An example of a descriptive markup language for electronic documents is specified by the ISO Standard 8879: "Standard Generalized Markup Language", or, "SGML". SGML is a
25 markup language that uses tags to prepare structured documents.

In a document prepared in accordance with SGML, an element has a begin tag and its content, and an end tag, when necessary. For example, a document may use the embedded begin and end tags

5 <para> and </para>, respectively, where "para" is the tag name corresponding to a paragraph element, to delimit paragraphs. The content may include text and other elements.

10 A structured document can be associated with a rule-base which defines the legal structures that the document can have. Such a rule-base is called a document type definition (DTD). For each element type, the DTD provides a general rule which governs the content of elements of the rule type. Also provided is an attribute definition rule which specifies an attribute name, type and optional default value for a given element. Thus, the DTD describes the characteristics and properties associated with each element type, and which sub-elements are valid within any given element.

25 A general rule can be unrestrictive. That is, there are no restrictions on what elements of the rule type can contain. An unrestricted general rule can be written as "ANY". A general rule can also be restrictive, specifying order and occurrence within the content of an element type. The restrictive general rule is stated in an expression language for specifying allowed patterns of sub-structures. Using the expression language, a restrictive general rule can be written as an expression with grouping operators (parenthesis), joining operators (commas for an ordered sequence and or-bars for an unordered sequence), and occurrence operators (a question mark for zero or one, an asterisk for zero or more, and a plus sign for one or more). For instance, the restrictive general rule

5 "head, para+" requires that the content be a head element followed by one or more para elements. As another example, "(para | figure)*" is interpreted to allow any number of paragraphs and/or figures in any order.

SUMMARY

10 In one aspect of the invention, a method of generating a document type definition (DTD) for a collection of source documents includes identifying patterns common to each source document in the collection of source documents and constructing for an element type in the collection of source documents a restrictive general rule based on the identified common pattern. The common patterns are identified by identifying common element sub-structures and attributes, i.e., attribute names and types as well as attribute values to be applied to the common attributes. The construction of the restricted general rule includes constructing a content model that specifies the sequence order and number of occurrences of sub-elements within the common pattern. It further includes constructing attribute definitions and value rules for each identified common attribute name and type.

25 In another aspect of the invention, the method identifies those patterns found to achieve a predetermined threshold of commonness (so-called "threshold patterns") and constructs for element types in the collection of source documents a restrictive general rule based on the identified threshold patterns.

5

10

In yet another aspect of the invention, a method of converting a format of a first source document to a format of a similarly structured second source document comprises identifying patterns common to the first and second source documents and mapping elements and sub-elements in the common pattern of the first source document to equivalent elements and sub-elements in the common pattern in the second source document. The method replaces tag names for each of the elements and sub-elements in the first source document with the tag names of the equivalent elements and sub-elements in the second source document.

The definition generation technique provides a single document type definition against which an entire set of same-structured source documents may be validated. Moreover, users producing new documents to be added to the set may use the DTD to ensure that mandatory sub-elements and attribute specifications are always provided. Thus, any newly produced documents are automatically valid.

25

The mapping process allows documents that are authored in one format, e.g., word processing or publishing format, to be converted to a second format automatically, i.e., without user intervention. Such an automated DTD mapping process is most beneficial when document format conversions involve a significant amount of document processing effort. For example, a publisher may find it desirable to convert documents from an "in-house" DTD (such as XML) to HTML for Web delivery or re-engineer its internal documentation around a different DTD.

BRIEF DESCRIPTION OF THE DRAWINGS

5 The above features and advantages of the present invention will become more apparent from the following detailed description taken in conjunction with the accompanying drawings, in which:

FIG. 1A is a flow diagram of a document type definition (DTD) building process.

10 FIG. 1B is a flow diagram of the common pattern identification process (of FIG. 1A) as it pertains to attributes-based patterns

FIG. 1C is a flow diagram of the restrictive general rule construction process of the DTD building process of FIG. 1A.

FIGS. 2-4 are hierarchical representations of two source documents for which a DTD is constructed in accordance with the DTD building process of FIG. 1A.

FIG. 5 is a flow diagram of a DTD mapping process.

FIG. 6 is a hierarchical representation of a source document to be processed by the DTD mapping process of FIG. 5.

FIG. 7 is a post-processing, hierarchical representation of the source document depicted in FIG. 6.

25 FIG. 8 is a block diagram of a computer system for supporting a electronic document publishing system including the DTD building process and DTD mapping process, as shown in FIG. 1A and FIG. 5, respectively.

DESCRIPTION

Referring to FIG. 1A, a document type definition (DTD) building process 10 is shown. The process receives 12 as input one or more source documents. Each source document uses identical tag names for the same purpose (e.g., both use "para" to define certain text as a "paragraph"). Such source documents are understood and processed as tree-like structures, with each element type represented as a tree node. If trees corresponding to the source documents are not defined in the source documents themselves or stored in a separate file, the DTD building process will parse 14 the source documents to build tree structures for each of the source documents. The DTD building process scans 16 the tree structures of the source documents to identify common patterns.

In the embodiment described herein, a pattern is a sub-structure, such as a particular occurrence of an element and one or more of its sub-elements. Preferably, patterns may capture particular element attribute information, i.e., names, types and restricted values, as well.

To perform the task of identifying common patterns, the process 10 invokes a matching process, which may be implemented as any one of a number of known pattern matching algorithms. For details of such pattern matching algorithms, reference may be had to a book by Donald E. Knuth, entitled "The Art of Computer Programming," (Reading, Mass; Addison-Wesley, 1973), as well as other sources. Having identified the common patterns, the DTD building process 10 constructs 18 a restrictive general rule for

each element type based on the identified common patterns.

Referring to FIG. 1B, one aspect of identifying common patterns 16, that is, identifying common patterns which are based 5 on attribute names, types and restricted values, is shown. The process determines 20 the number of occurrences of each attribute name on an element type and examines 22 the attribute values for each occurrence of each attribute name on the same element type to determine the attribute type. Additionally, the process may 10 determine if the attribute occurs globally in a document or only on individual named element types. It determines 24 if the attribute name occurs in association with the same attribute value on more than one element type. To make such a determination, it will look at whether an attribute/value pair occurs on more than one element type. It can establish a standard deviation and test each source document in the collection against the standard deviation. For a given attribute type (as previously determined), the process examines 26 attribute values for each occurrence of the attribute type in all of the source documents and establishes 28 an enumeration or a restricted range appropriate to the attribute type.

Referring now to FIG. 1C, constructing 18 a restrictive general rule includes constructing 32 a content model to specify any sequence order/occurrence constraints associated with sub- 25 elements occurring within the pattern (i.e., the common sub-elements), as well as constructing 34 attribute definitions and value rules for common attributes. The attribute definitions specify the association between attribute names and elements. The value rules specify the values that may be applied to

particular named attributes. A specified value may be an enumeration, a set, a range or boolean expression.

It is preferable to modify the above-described process 5 to take into account those patterns that are shared by only some portion of the source documents. Such patterns are those that have achieved some predetermined threshold level of commonness, hereinafter referred to as "threshold patterns". The process 10 so modified would identify threshold patterns in 10 addition to common patterns (at 16) and construct the restrictive general rules 18 to include the identified threshold patterns. Patterns which are below the predetermined threshold would not be included in the constructed rule. Suppose that a threshold is set at 10%. Consider then, for example, two documents having a total of 8 section elements between them. Each section element contains one or more paragraph elements. If there is one section element that does not begin with a head element, then the pattern is at 12.5% (above the threshold) and the DTD building process constructs for the section element type the restrictive general rule "head?, para+". In contrast, a pattern in which a section element immediately begins with a head element occurring in all but one out of fifteen section elements is at 6.6%, well below the threshold. Consequently, the DTD building process ignores the pattern and generates the rule "head, para+" for the section 25 element type.

Optionally, the identification of common sub-structures may involve the application of a standard deviation test to determine "commonness" of patterns within a given source document. Given a statistically significant sample, any pattern

which falls outside of the standard deviation from the mean can be either discarded or re-coded with local restrictive general rules to override the restrictive general rules of the DTD.

5 Additionally, heuristic methods may be used to detect certain patterns as being erroneously generated or ill-formed, and therefore capable of being discarded.

10 The restrictive general rules, once constructed, are available for encoding in a document type definition template or file by a user of a system such as an electronic document publishing system.

15 It is important to consider that many electronic documents are provided with one or more style sheets specifying format characteristics for their display. A style sheet includes format characteristics for each type of element in a document. The format characteristics may include font styles and size, margins and other details relating to the appearance and behavior of a document. Because style sheets are often stored separate from their corresponding documents, it may be necessary or desirable to construct a style definition for a collection of such documents. Although the process 10 has been described above with reference to document type definitions, it is not so limited. It should be understood that the process 10 is a definition building process that is equally applicable to 20 constructing style definitions for a set of style sheets.

25 FIGS. 2-4 depict logical, hierarchical representations of two exemplary source documents that are received as input by the DTD building process 10. In FIGS. 2-4, like reference numerals are used in association with like elements and sub-

elements.

Referring first to FIG. 2, a first source document 50 and a second source document 52 are shown. The structure of 5 first source document 50 includes a root document element 54a. The root document element 54a contains two section elements 56a and 56b, followed by an index element 58. The section element 56a contains a head element 60a, followed by para elements 62a and 62b, figure element 64a, and para elements 62c and 62d. The 10 section element 56b contains a head element 60b, followed by para elements 62e and 62f.

The structure of the second source document 52 includes a root document element 54b. The root document element includes three sections elements, section elements 56c, 56d and 56e, respectively. The section element 56c includes a head element 60c, followed by three para elements 62g, 62h and 62i, respectively. The section element 56d includes a head element 60d, followed by a para element 62j and a figure element 64b. The third section element 56e includes a head element 60e followed by a para element 62k.

Referring to FIG. 3, the hierarchical representations of the source documents 50 and 52 (from FIG. 2) are shown with first level sub-structures 66a, 66b identified as being common to both documents 50 and 52 highlighted by bolded lines. In the 25 common (first level) sub-structure 66a of document 50, the document element 54a includes the section elements 56a and 56b. In the common (first level) sub-structure of document 52, the document element 54b includes sections 56c, 56d and 56e. The occurrence of index element 58 following sections (sections 56a

and 56b) is not common.

The DTD building process 10 (FIG. 1A) constructs the restrictive general rule "section+, index?" for the document element 54 (i.e., 54a and 54b, collectively) based on the identified pattern. This restrictive general rule thus defines the document element 54 as containing one or more section elements followed by zero or one index element. Had there been a third source document which contained no sections within its document element, the process would have constructed the rule "section*, index?". The expression "section*, index?" is interpreted as zero or more section elements, followed by zero or one index element. Similarly, had a fourth document contained an index followed by a section, the rule would be constructed as "(section | index)*", thus requiring any number of section and/or index elements occurring in any order.

Referring now to FIG. 4, in addition to the first level sub-structures 66a and 66b, second level sub-substructures 68a, 68b are shown highlighted by bolded lines. Each section element (the section elements 56a through 56e) contains as sub-elements a head element, followed by a varied number of para elements. Additionally, the section elements 56a and 56d have figure elements 64a and 64b, respectively.

The DTD building process 10 (FIG. 1A) constructs for the section element type 56 (section elements 56a through 56e, collectively) the restrictive general rule "head, (para | figure)+". That is, a head element is followed by one or more para and/or figure elements. Alternatively, a tighter rule may be constructed. For example, the DTD building process could

construct the restrictive general rule "head, para, (figure | para)*", which disallows a head followed by a figure.

5 After processing all common patterns shown in the representations of FIGS. 3 and 4, the DTD building process 10 will have constructed the following set of restrictive general rules for the source documents 50 and 52:

10 doc = section+, index?
section = head, (para | figure)+
index = <TEXT>
head = <TEXT>
para = <TEXT>
figure = <TEXT>

These rules can be included in an available document type definition template or file.

Referring now to FIG. 5, a DTD mapping process (or mapping process) 70 is shown. The DTD mapping process 70 is used to convert one or more "orphan" documents to the same format as another document or set of documents. For example, a publisher may wish to integrate into a set of electronic technical manuals a document that was produced electronically by another publisher in a different format. In yet another example, some documents in a set of documents may have been updated in a different format from that of the original set and it may be desirable to unify 25 the entire set under the new format. In these typical scenarios, the process would convert the DTD of the "orphan" document (or documents) to a target DTD, that is, the DTD associated with second document or set of documents having the format to which the document set publisher wishes to conform the orphan document

or documents. Simply stated, the goal is to make a first document or set of documents look like a second document or set of documents.

5 The DTD mapping process 70 examines 72 the document type definitions of a first and a second source document to identify common patterns. As mentioned earlier (with respect to the DTD building process 10), patterns may include elements, sub-elements and corresponding attributes (or more particularly, 10 attribute types, names and values). The DTD mapping process 70 maps 74 equivalencies between elements and sub-elements in the common pattern of the first source document and elements and sub-elements in the common pattern in the second source document. Once the DTD mapping process 70 has mapped elements and sub-elements of the first source document with elements and sub-elements of the second source document, the DTD mapping process 70 changes 76 the tag names of each element and sub-element in the first source document to the equivalent element and sub-element of the second source document.

20 If the source DTD, i.e., the DTD for a collection of documents to be recoded via the target DTD, does not exist, the DTD mapping process 70 needs to construct it. The source DTD can be constructed according to the DTD building process 10 of FIG. 1A.

25 It should be noted that the common pattern identification procedure 70 (FIG. 5) involves pattern and/or heuristics matching techniques and may be bounded by the user according to user-specified criteria.

Referring to FIG. 6, a hierarchical representation of a

exemplary structured source document 80 to be recoded (or
"retagged") according to a target DTD, in this case, the DTD
constructed for the source documents 50, 52 depicted in the
5 representations of FIGS. 2-4, is shown. The structure of the
source document 80 shown in FIG. 6 will now be described. A
"pub" element 82 contains two "chapter" elements 84a and 84b.
The "chapter" element 84a includes a heading element 86a
following by two "body" elements 88a-b. The body elements 88a-b
10 are followed by a graphic element 90, which is in turn followed
by another body element 88c. The chapter element 84b includes a
heading element 86b and two body elements 88d and 88e.

The source document 80 may be associated with the
following document type definition:

```
pub = chapter+
chapter = heading, (body | graphic)+  
heading = <TEXT>  
body = <TEXT>  
graphic = <TEXT>
```

Recall that the document type definition constructed for the
structured documents 50 and 52 (from FIGS. 2-4) is as follows:

```
doc = section+, index?  
section = head, (para | figure)+  
index = <TEXT>  
head = <TEXT>  
para = <TEXT>  
figure = <TEXT>
```

The DTD mapping process 70 (FIG. 5) examines, e.g.,
compares, 72 the two document type definitions, that is, the DTDs

for the source document 80 and the DTD corresponding to the source documents 50 and 52, looking for common patterns. The DTD mapping process determines that the general rules for "section" and "chapter" have the same pattern, and that doc and pub have similar patterns. Alternatively, and as discussed above in reference to FIG. 5, the DTD mapping process might also use heuristics to find common sub-structures. For instance, element types with the same stem (e.g., "head" and "heading") might be equated.

The DTD mapping process 70 identifies 72 common patterns and maps 74 elements and sub-elements of the DTD for source document 80 to equivalent elements and sub-elements of the DTD constructed for the source documents 50 and 52. The equivalent element types are as follows:

pub ~ doc
chapter ~ section
heading ~ head
body ~ para
graphic ~ figure

The DTD mapping process recodes 76 source document 80, using the equivalent element types from the DTD constructed for the source documents 50 and 52. In other words, the tag names for the elements in source document 80 are changed to the tag names for the equivalent elements of the target DTD. The resulting source document is depicted in FIG. 7 as a source document 90.

Referring to FIG. 7, the structure of the source document 90 (i.e., recoded source document 80 of FIG. 6) is now described. It should be noted that reference numbering

convention for FIGS. 2-4 has been adopted in FIG. 7. A doc element 54c contains section elements 56f-g. The doc element 54c and section elements 56f-g are the "retagged" versions of the pub element 82 and chapter elements 84a, 84b, respectively. The section element 56f includes a head element 60f (formerly, "heading" 86a), two paragraph elements 62l and 62m (formerly, "body" elements 88a, 88b, respectively), a figure element 64c (formerly, "graphic" element 90) and another paragraph element 10 62n (formerly, body element 88c). The section element 56g includes, as sub-elements, a head element 60g, followed by paragraph elements 62o and 62p. Sub-elements 60g, 62o and 62p correspond to the sub-elements 86b, 88d and 88e, respectively, of the original source document 80.

Referring to FIG. 8, a computer system 100 for supporting the DTD building and mapping processes, as well as any matching or other processes invoked by these processes, is shown. The invention may be implemented in digital electronic circuitry or in computer system hardware, firmware, software, or in combinations of them. Apparatus of the invention may be implemented in a computer program product tangibly embodied in a machine-readable storage device for execution by a computer processor 102; and method steps of the invention may be performed by the computer processor 102 executing a program to perform 25 functions of the invention by operating on input data and generating output.

Suitable processors include, by way of example, both general and special purpose microprocessors. Generally, the processor 102 will receive instructions and data from a read-only

memory (ROM) 104 and/or a random access memory (RAM) 106 through a CPU bus 108. A computer can generally also receive programs and data from a storage medium such as an internal disk 110 5 operating through a mass storage interface 112 or a removable disk 114 operating through an I/O interface 116. The flow of data over an I/O bus 118 to and from I/O devices 110, 114, 120, 122 and the processor 102 and memory 104, 106 is controlled by an I/O controller 124. User input is obtained through a keyboard 10 120, mouse, stylus, microphone, trackball, touch-sensitive screen, or other input device. These elements will be found in a conventional desktop computer as well as other computers suitable for executing computer programs implementing the methods described here, which may be used in conjunction with any display device 122, or other raster output device capable of producing color or gray scale pixels on paper, film, display screen, or other output medium.

Storage devices suitable for tangibly embodying computer program instructions include all forms of non-volatile memory, including by way of example semiconductor memory devices, such as EPROM, EEPROM, and flash memory devices; magnetic disks such as internal hard disks 110 and removable disks 114; magneto-optical disks; and CD-ROM disks. Any of the foregoing may be supplemented by, or incorporated in, specially-designed ASICs 25 (application-specific integrated circuits).

Typically, the DTD building, mapping and other related processes are components of an electronic document publishing system residing on the internal disk 110. These electronic document publishing system processes are executed by the

processor 102 in response to a user request to the computer system's operating system (not shown) after being loaded into memory. The source documents processed by these electronic document publishing system processes may be retrieved from a mass storage device such as the internal disk 110 or other local memory, such as RAM 116 or ROM 104. It is also possible that the source documents could reside on and thus be retrieved from another computer system, such as a Web server.

10

Other Embodiments

It is to be understood that while the invention has been described in conjunction with the detailed description thereof, the foregoing description is intended to illustrate and not limit the scope of the invention, which is defined by the scope of the appended claims. Other aspects, advantages, and modifications are within the scope of the following claims. For example, although the invention has been described with reference to an SGML-based implementation, it is not so limited. It should be understood that the invention is equally applicable to other languages and syntaxes that incorporate concepts like those found in SGML.

What is claimed is:

25

CLAIMS

1 1. A method of generating a definition for a collection of
2 source documents comprising:

3 identifying patterns common to each source document in
4 the collection of source documents; and

5 constructing for an element type in the collection of
6 source documents a restrictive general rule based on the
7 identified common patterns.

1 2. The method of claim 1, wherein identifying common
2 patterns comprises:

3 identifying common attribute names and types.

4 3. The method of claim 2, wherein identifying common
5 patterns further comprises:

6 identifying restricted attribute values associated with
7 the common attribute names and types.

8 4. The method of claim 2, wherein identifying common
9 attribute names and types comprises:

10 determining the number of occurrences of each attribute
11 name on an element type;

12 examining the attribute values for each occurrence of
13 each attribute name on the same element type to determine the
14 attribute type; and

15 determining if the attribute name occurs in association
16 with the same attribute value on more than one element type.

1 5. The method of claim 3, wherein identifying restricted
2 attribute values comprises:

3 examining attribute values for each occurrence of an
4 attribute type in all of the source documents in the collection
5 of source documents; and

6 establishing an enumeration or a restricted range
7 appropriate to the attribute type.

1 6. The method of claim 5, wherein identifying restricted
2 attribute values further comprises:

3 applying a heuristic to identify errors in the
4 collection of source documents; and

5 adjusting the established enumeration or restricted
range for attribute values.

7. The method of claim 1, wherein constructing a
restricted general rule comprises:

constructing a content model that specifies the
sequence order and number of occurrences of sub-elements within
the common pattern.

1 8. The method of claim 2, wherein constructing a
2 restricted general rule comprises:

3 constructing attribute definitions and value rules for
4 each identified common attribute name and type.

1 9. The method of claim 1, further comprising:
2 identifying those patterns found to achieve a
3 predetermined threshold of commonness; and
4 constructing a restrictive general rule for those
5 identified patterns.

10. A computer program residing on a computer-readable
medium for building a document type definition for a collection
of source documents, the computer program comprising instructions
causing a computer system to:

 identify patterns common to each source document in the
collection of source documents; and

 construct for an element type in the collection of
source documents a restrictive general rule based on the
identified common patterns.

11. The computer program of claim 10, wherein the
instructions to identify common patterns comprise instructions
to:

 identify common attribute names and types.

12. The computer program of claim 11, wherein the
instructions to identify common patterns further comprise
instructions to:

 identify restricted attribute values associated with
the common attribute names and types.

13. A computer system comprising:
a storage device for storing a set of source documents;
and

a computer processor configured by a document type definition building program to identify patterns common to each source document in the set of source documents and construct for an element type in the set of source documents a restrictive general rule base on the identified common patterns.

1 14. A method of converting a format of a first source
2 document to a format of a similarly structured second source
3 document, the method comprising:

4 identifying patterns common to the first and second
5 source documents; and

6 using the identified common patterns to map elements
7 and sub-elements in the first source document to equivalent
8 elements and sub-elements in the second source document.

15. The method of claim 14, further comprising:

16. replacing tag names for each of the elements and sub-elements in the first source document with equivalent tag names of the elements and sub-elements in the second source document.

1 16. The method of claim 14, wherein identifying patterns
2 common to the first and second source documents comprises:
3 examining document type definitions for the first and
4 second source documents.

1 17. The method of claim 16, further comprising:
2 producing the document type definition for the first
3 source document if the document type definition for the first
4 source document does not already exist.

1 18. The method of claim 14, wherein identifying patterns
2 common to the first and second source documents comprises:
3 performing pattern matching.

1 19. The method of claim 14, wherein identifying patterns
2 common to the first and second source documents comprises:
3 matching heuristics of the patterns in the first source
4 document to heuristics of the patterns in the second source
5 document.

20. The method of claim 18, wherein identifying patterns
common to the first and second source documents further
comprises:

1 matching heuristics of the patterns in the first source
2 document to heuristics of the patterns in the second source
3 document.

7 21. The method of claim 14, wherein using uses the
8 identified common patterns to map automatically elements and sub-
9 elements in the first source document to equivalent elements and
10 sub-elements in the second source document.

1 22. A method of converting the format of a source document

2 to the format of a set of source documents, the set of source
3 documents having a structure similar to the first source
4 document, the method comprising:

5 identifying patterns common to the source document and
6 the set of source documents;

7 mapping elements and sub-elements in the common pattern
8 of the source document to equivalent elements and sub-elements
9 the common pattern of the set of source documents; and

10 replacing tag names for each of the elements and
11 sub-elements in common pattern of the source document with the
12 equivalent tag names of the elements and sub-elements in common
13 pattern of the set of source documents.

23. The method of claim 22, wherein identifying patterns
common to the source document and the set of source documents
comprises:

24. examining document type definitions for the source
document and the set of source documents.

25. The method of claim 23, further comprising:

26. producing the document type definition for the source
document if the document type definition for the source document
27 does not already exist.

28. A computer program residing on a computer-readable
29 medium for converting a format of a first source document to a
30 format of a similarly structured second source document, the
31 computer program comprising instructions causing a computer

5 system to:
6 identify patterns common to the first and second source
7 documents; and
8 use the identified common patterns to map elements and
9 sub-elements of the first source document to equivalent elements
10 and sub-elements of the second source document.

11 26. The computer program of claim 25, further comprising
12 instructions to:

13 replace tag names for the each of the elements and sub-
14 elements in the common pattern of the first source document with
15 equivalent tag names of the elements and sub-elements in the
16 common pattern of the second source document.

17 27. The computer program of claim 26, wherein the
18 instructions to identify patterns common to the source document
19 and the set of source documents comprise instructions to:

20 examine document type definitions for the source
21 document and and the set of source documents.

22 28. A computer system comprising:

23 a storage device for storing a source document and a
24 set of source documents, the source document having a format
25 different from that of the set of source documents; and

26 a computer processor configured by a mapping program to
27 identify patterns common to the source document and the set of
28 source documents and map elements and sub-elements in the common
pattern of the source document to equivalent elements and sub-

elements the common pattern of the set of source documents.

ABSTRACT OF THE DISCLOSURE

A method of generating a definition for a collection of source documents is provided. Patterns common to each source document in the collection of source documents are identified and restrictive general rules based on the identified common patterns are then constructed for element types. The construction of a restricted general rule includes constructing a content model that specifies the sequence order and number of occurrences of sub-elements within the common pattern. It further includes constructing attribute definitions and values rules for attributes occurring in the common patterns. Also provided is a method of converting a format of a first source document to a format of a similarly structured second source document is provided. The method identifies patterns common to the first and second source documents and maps elements and sub-elements in common pattern of the first source document to equivalent elements and sub-elements in the common pattern of the second source document.




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6.





FIG. 7

FIG. 8



COMBINED DECLARATION AND POWER OF ATTORNEY

As a below-named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

METHOD OF CONSTRUCTING A DOCUMENT TYPE DEFINITION FROM A SET OF STRUCTURED ELECTRONIC DOCUMENTS

the specification of which:

[x] is attached hereto.

[] was filed on _____.

[] under Application No. _____.
[] with Express Mail No. _____ (Application Number not yet known).

[] was described and claimed in PCT International Application No. _____.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, code of Federal Regulations, Section 1.56(a).

I hereby appoint the following attorneys and/or agents to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith, and direct that all correspondence be addressed to that Customer Number:

Customer Number 021876

Address all telephone calls to **Denis G. Maloney** at telephone number 617/542-5070.

Address all correspondence to **Roger S. Borovoy, Fish & Richardson P.C.**, 2200 Sand Hill Road, Suite 100, Menlo Park, CA 94025.

For Assigned Inventions: I understand that the purpose of making this appointment is to permit prosecution of patent applications for the above-identified invention for the benefit of my assignee, and that this appointment does not create an attorney-client relationship between me and these appointees.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of inventor:

Jeff Young

Inventor's signature



Date:

2/11/99

Residence:

948 El Rio Drive, San Jose, CA 95125

Citizen of:

USA

Post Office Address:

948 El Rio Drive, San Jose, CA 95125

Full name of inventor:

Joel A. Nava

Inventor's signature

Date:

Residence:

2883 Benjamin Avenue, San Jose, CA 95124

Citizen of:

USA

Post Office Address:

2883 Benjamin Avenue, San Jose, CA 95124

COMBINED DECLARATION AND POWER OF ATTORNEY

As a below-named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

METHOD OF CONSTRUCTING A DOCUMENT TYPE DEFINITION FROM A SET OF STRUCTURED ELECTRONIC DOCUMENTS

the specification of which:

[x] is attached hereto.

[] was filed on _____.

[] under Application No. _____.

[] with Express Mail No. _____ (Application Number not yet known).

[] was described and claimed in PCT International Application No. _____.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, code of Federal Regulations, Section 1.56(a).

I hereby appoint the following attorneys and/or agents to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith, and direct that all correspondence be addressed to that Customer Number:

Customer Number 021876

Address all telephone calls to Denis G. Maloney at telephone number 617/542-5070.

Address all correspondence to Roger S. Borovoy, Fish & Richardson P.C., 2200 Sand Hill Road, Suite 100, Menlo Park, CA 94025.

[X] For Assigned Inventions: I understand that the purpose of making this appointment is to permit prosecution of patent applications for the above-identified invention for the benefit of my assignee, and that this appointment does not create an attorney-client relationship between me and these appointees.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of inventor: Jeff Young

Inventor's signature _____ Date: _____

Residence: 948 El Rio Drive, San Jose, CA 95125
Citizen of: USA
Post Office Address: 948 El Rio Drive, San Jose, CA 95125

Full name of inventor: Joel A. Nava

Inventor's signature _____ Date: 3/2/99

Residence: 2883 Benjamin Avenue, San Jose, CA 95124
Citizen of: USA
Post Office Address: 2883 Benjamin Avenue, San Jose, CA 95124